

MANUAL FERROUS COLDSAWS CS AND FK350 SERIES

CS SERIES FEATURES

- Heavy duty cast iron frame base standard
- Cast dual pivot saw head
- Hardened and ground worm and wheel gear box
- Two cutting speeds
- 1.3 gallon coolant tank capacity

FK350 FEATURES

- Sturdy gear box design
- Double self centering vise for burr free cuts
- Thermal overload protection with magnetic starter
- 350mm Ferrous cold saw for steel, stainless and tough to cut alloys
- Manually cuts from 45° left to 45° right
- Miter stops at 90°, 45° left to 45° right
- Two cutting speeds



CS-275



FK350



STOCK NUMBER	414226	414227	414214	414217
Model Number	CS-275	CS-315	J-FK350-2K	J-FK350-4K
CUTTING CAPACITY FOR TUBING				
Round at 90° (in.)	3-5/16	3-1/2	4-1/2	4-1/2
Round at 45° (in.)	3-5/16	3-1/2	3-1/2	3-1/2
Square at 90° (in.)	2-1/2 x 2-1/2	3-1/4 x 3-1/4	4-1/4	4-1/4
Square at 45° (in.)	2-1/4 x 2-1/4	2-5/8 x 2-5/8	3-1/2	3-1/2
Rectangle at 90° (in.)	3 x 2	4 x 3-1/4	5-1/2 x 3-3/4	5-1/2 x 3-3/4
Rectangle at 45° (in.)	2-1/4 x 2-5/16	3-1/4 x 2-5/8	3-1/2 x 3-1/2	3-1/2 x 3-1/2
CUTTING CAPACITY FOR SOLID				
Round at 90° (in.)	3-1/3	3-1/2	2	2
Round at 45° (in.)	3-1/3	3-1/2	1-3/4	1-3/4
Square at 90° (in.)	2-1/2 x 2-1/2	3-1/4 x 3-1/4	2	2
Square at 45° (in.)	2-1/4 x 2-1/4	2-5/8 x 2-5/8	1-3/4	1-3/4
Blade Size (mm)	275 x 32 x 2	315 x 32 x 2	350 x 32 x 2.5	350 x 32 x 2.5
Blade Speeds (RPM)	54, 108	52, 104	44, 88	44, 88
Maximum Vise Opening (in.)	4	4-3/4	6	6
Motor	1.5HP, 230V, 3Ph	2HP, 230V, 3Ph	2HP, 230V, 3Ph	2HP, 460V, 3Ph
Floor Space required (in./ L x W x H)	38 x 37 x 64	39 x 37 x 69	50 x 28 x 60	50 x 28 x 60
Net Weight (lbs.)	350	390	794	794

