



A5816



A5836



15" VARIABLE SPEED DRILL PRESSES

- Speeds from 400 to 5,000 RPM
- Handwheel adjustment sets the speeds
- Large 2-1/4" quill allows greater accuracy
- 3" column diameter for maximum head support
- Full bearing support on quill for maximum spindle stiffness
- 6" stroke for deep hole applications
- Accurate depth stop for precise hole depths
- 1/2" Drill chuck and arbor
- Safety collar



STOCK NUMBER

A5816/A5818

A5836/A5838

Type	15" Floor	15" Bench
Drills to Center of Circle (in.)	15	15
Cast Iron Drilling Capacity (max./in.)	5/8	5/8
Steel Drilling Capacity (max./in.)	1/2	1/2
Column Diameter (in.)	3	3
Quill Diameter (in.)	2-1/4	2-1/4
Spindle Taper	2 MT	2 MT
Spindle Travel (in.)	6	6
Spindle Speeds (RPM)	400 to 5000	400 to 5000
Overall Table Size (in.)	15-1/4 x 17-3/4	14-1/4 x 21
Table Working Surface (in.)	12-1/2 x 14-1/2	10-5/8 x 12-3/8
T-slot Number & Size (in.)	2 & 1/2	2 & 1/2
Spindle to Table (in.)	41	
Spindle to Base (in.)	47-1/2	11
Overall Height (in.)	67-1/2	36-1/2
Motor A5816/A5836	1 HP, 115/230V, 1Ph, Prewired 115V	1 HP, 115/230V, 1Ph, Prewired 115V
Motor A5818/A5838	1HP, 230/460V, 3Ph, Prewired 230V	1HP, 230/460V, 3Ph, Prewired 230V
Floor Space Required (in./L x W x H)	30 x 20 x 71	
Net Weight (lbs.)	426	336

*Capacities for continuous production use will vary based on application